

Metal Series

Housing and Trim: Die-cast aluminium
 Mounting type: Surface
 Body: White and black finish
 Heat Management: Die-cast aluminium heat sink
 Reflector: Silver, white, black and gold, adjustable angle
 Diffuser: PMMA Lens

LED Modules
 GERMAN Technology
 Comfort COB - Up to 3300lm
 Long service life time : 50,000 hours (L80/B10)
 Ambient temperature - 40°C to +40°C

Drivers: 150mA / 300mA / 500mA / 600mA
 (optional: Dimmable available)
 Power factor at full load : 0.97
 SELV , Low Ripple current < 1% ,THD <15%
 Warranty: 5 years

Standards
 EN 620301: LED modules for general lighting - Safety specification
 EN 62471: Photobiological safety of lamps and systems
 EN 55015: Radio disturbance emissions
 EN 61000-3-2 Limited for harmonic emissions
 EN 61547: Immunity requirements



Powered by:



Application: Commercial Building, Lobby, Conventional Hall, Ballroom, Concourse

Model	Wattage	Voltage	Frequency	Power Factor	Colour	Colour Temperature	Module Luminous Flux (Lm)	Module Efficacy Lm/W	Typ. Beam Angle	Typ. CRI Ra	Energy Efficiency	Dimension(Dia x H) mm
M2-38-4W	4.2W	220-240	50/60Hz	0.95	Warm white	2700K	615	148	15°/30°/45°	>82	A+	75 x 115
					Warm white	3000K	645	155	15°/30°/45°	>82	A+	
					Neutral white	4000K	665	160	15°/30°/45°	>82	A+	
					Cool white	5700K	670	161	15°/30°/45°	>82	A+	
M2-38-10W	10.6W	220-240	50/60Hz	0.95	Warm white	2700K	1270	120	15°/30°/45°	>82	A+	100 x 135
					Warm white	3000K	1340	126	15°/30°/45°	>82	A+	
					Neutral white	4000K	1380	130	15°/30°/45°	>82	A+	
					Cool white	5700K	1390	131	15°/30°/45°	>82	A+	
M2-38-17W	17.3W	220-240	50/60Hz	0.95	Warm white	2700K	2585	149	15°/30°/45°	>82	A+	120 x 145
					Warm white	3000K	2725	158	15°/30°/45°	>82	A+	
					Neutral white	4000K	2805	162	15°/30°/45°	>82	A+	
					Cool white	5000K	2860	165	15°/30°/45°	>82	A+	
					Cool white	5700K	2830	164	15°/30°/45°	>82	A+	
M2-38-21W	21.2W	220-240	50/60Hz	0.95	Warm white	2700K	3030	143	15°/30°/45°	>82	A+	140 x 165
					Warm white	3000K	3185	151	15°/30°/45°	>82	A+	
					Neutral white	4000K	3280	155	15°/30°/45°	>82	A+	
					Cool white	5000K	3345	158	15°/30°/45°	>82	A+	
					Cool white	5700K	3315	157	15°/30°/45°	>82	A+	

*Colour tolerance: 3 MacAdam **Production tolerance of luminous flux and efficiency: ±10% ***Min. CRI ±3% ****Power consumption: ±10%
 The values contained in this data sheet can change due to technical innovations without notifications, therefore kindly refer to us when during order.