



Mariner Mini Weatherproof Fixture

Product Features

The Mariner Mini weather proof fixture has an attractive, neutral aesthetics that makes it suitable for applications in both commercial, residential and industrial environments. It is an energy-efficient, low maintenance alternative solution to traditional fluorescent waterproof fixtures. The Mariner offers customers the best mix of value and performance. It has compact size with high lumen output and completely integrable lighting solution for applications with high requirements for luminous intensity and resistance.

Specification :

LED & Optical

- Output Range : 1200 – 5600lm
- Photometric Options : 120 degree
- System Efficacy : Up to 100LPW
- CCT : 4000K/6500K @ 70CRI

Electrical

- Input voltage : 220-240V_{AC}
- Input Frequency :50/60Hz
- Power Factor >0.9
- Warranty : 2 Years

Ratings

- IP Rated : IP65
- Working Temperature : -20°C – 45°C

Construction & Finishing

- Impact resistant body and polycarbonate cover
- UV Stabilized, flame retardant PC with good color stability under heat exposure.

Applications

- Underground Parking Bay
- Industrial Warehouse
- Pathway
- Corridor walkway

SKU#	Description	Watt (W)	CCT(K)	Lumen (lm)	Beam Angle	LPW	Voltage (V)	Dimension (mm)	Lifetime (hrs)	Qty/Ctn
70349	LMR7212N2ftV1-CW	12	6500K	1200	120°	100	220 -240	600 x 72 x 58	30k	20pcs/Box
70350	LMR7225N2ftV1-CW	24	6500K	2400	120°	100	220 -240	600 x 92 x60	30k	15pcs/Box
70351	LMR7425N4ftV1-CW	24	6500K	2400	120°	100	220 -240	1200 x 72 x 58	30k	12pcs/Box
70352	LMR7450N4ftV1-CW	48	6500K	4400	120°	92	220 -240	1200 x 92 x 60	30k	8pcs/Box
70353	LMR7530N5ftV1-CW	28	6500K	2800	120°	100	220 -240	1500 x 72 x 58	30k	12pcs/Box
70355	LMR7560N5ftV1-CW	56	6500K	5600	120°	100	220 -240	1500 x 92 x 60	30k	8pcs/Box
81901	LMR7212N2ftV1-NW	12	4000K	1200	120°	100	220 -240	600 x 72 x 58	30k	20pcs/Box
81902	LMR7225N2ftV1-NW	24	4000K	2400	120°	100	220 -240	600 x 92 x60	30k	15pcs/Box
81903	LMR7425N4ftV1-NW	24	4000K	2400	120°	100	220 -240	1200 x 72 x 58	30k	12pcs/Box
81904	LMR7450N4ftV1-NW	48	4000K	4400	120°	92	220 -240	1200 x 92 x 60	30k	8pcs/Box
81905	LMR7530N5ftV1-NW	28	4000K	2800	120°	100	220 -240	1500 x 72 x 58	30k	12pcs/Box
81907	LMR7560N5ftV1-NW	56	4000K	5600	120°	100	220 -240	1500 x 92 x 60	30k	8pcs/Box

