



Value Pro Retrofit Lamp



Every day value & performance perfect for basic LED lighting applications

In addition to GE's premium LED Lamps, there is now a value offering with basic performance to meet the needs of ultra competitive projects. The offering consists of high volume LED lamps including MR16 GU10, PAR Series Lamp

Value PRO LED Lamp Product Codes and Specifications



LED Bright Stik



Description	Watt (W)	Dimension, mm	CCT (K)	Lumens	LPW	Voltage	P.F	Beam Angle	CRI	Life Time (hrs)	Qty/Ctn
BST5W/A19/830/220-240V/E27/G4	5	Ø37 x 115	3000K	470	94	220 - 240	> 0.5	220°	80	15k	10pcs/Box
BST5W/A19/840/220-240V/E27/G4	5	Ø37 x 115	4000K	500	100	220 - 240	> 0.5	220°	80	15k	10pcs/Box
BST5W/A19/865/220-240V/E27/G4	5	Ø37 x 115	6500K	500	100	220 - 240	> 0.5	220°	80	15k	10pcs/Box
BST9W/A19/830/220-240V/E27/G4	9	Ø37 x 115	3000K	806	90	220 - 240	> 0.5	220°	80	15k	10pcs/Box
BST9W/A19/840/220-240V/E27/G4	9	Ø37 x 115	4000K	850	94	220 - 240	> 0.5	220°	80	15k	10pcs/Box
BST9W/A19/865/220-240V/E27/G4	9	Ø37 x 115	6500K	850	94	220 - 240	> 0.5	220°	80	15k	10pcs/Box
BST11W/A21/830/220-240V/E27/G4	11	Ø37 x 115	3000K	1055	96	220 - 240	> 0.5	220°	80	15k	10pcs/Box
BST11W/A21/840/220-240V/E27/G4	11	Ø45 x 137	4000K	1100	100	220 - 240	> 0.5	220°	80	15k	10pcs/Box
BST11W/A21/865/220-240V/E27/G4	11	Ø45 x 137	6500K	1100	100	220 - 240	> 0.5	220°	80	15k	10pcs/Box
BST14W/A21/830/220-240V/E27/G4	14	Ø45 x 137	3000K	1520	109	220 - 240	> 0.5	220°	80	15k	10pcs/Box
BST14W/A21/840/220-240V/E27/G4	14	Ø45 x 137	4000K	1600	114	220 - 240	> 0.5	220°	80	15k	10pcs/Box
BST14W/A21/865/220-240V/E27/G4	14	Ø45 x 137	6500K	1600	114	220 - 240	> 0.5	220°	80	15k	10pcs/Box

A60 Snowcone



Description	Watt (W)	Dimension, mm	CCT (K)	Lumens	LPW	Voltage	P.F	Beam Angle	CRI	Life Time (hrs)	Qty/Ctn
LED ECO A60/6W/830/E27	6	Ø60 x 108	3000K	470	78	220 - 240	> 0.5	200°	80	10k	1pcs/color box 12pcs/case
LED ECO A60/6W/840/E27	6	Ø60 x 108	4000K	500	83	220 - 240	> 0.5	200°	80	10k	1pcs/color box 12pcs/case
LED ECO A60/6W/865/E27	6	Ø60 x 108	6500K	500	83	220 - 240	> 0.5	200°	80	10k	1pcs/color box 12pcs/case
LED ECO A60/9.5W/830/E27	9.5	Ø60 x 108	3000K	810	85	220 - 240	> 0.5	200°	80	10k	1pcs/color box 12pcs/case
LED ECO A60/9.5W/840/E27	9.5	Ø60 x 108	4000K	850	89	220 - 240	> 0.5	200°	80	10k	1pcs/color box 12pcs/case
LED ECO A60/9.5W/865/E27	9.5	Ø60 x 108	6500K	850	89	220 - 240	> 0.5	200°	80	10k	1pcs/color box 12pcs/case
LED ECO A60/11.5W/830/E27	11.5	Ø60 x 115	3000K	1055	92	220 - 240	> 0.5	200°	80	10k	1pcs/color box 12pcs/case
LED ECO A60/11.5W/840/E27	11.5	Ø60 x 115	4000K	1150	100	220 - 240	> 0.5	200°	80	10k	1pcs/color box 12pcs/case
LED ECO A60/11.5W/865/E27	11.5	Ø60 x 115	6500K	1150	100	220 - 240	> 0.5	200°	80	10k	1pcs/color box 12pcs/case
LED ECO A60/14W/830/E27	14	Ø60 x 119	3000K	1521	109	220 - 240	> 0.5	200°	80	10k	1pcs/color box 12pcs/case
LED ECO A60/14W/840/E27	14	Ø60 x 119	4000K	1600	114	220 - 240	> 0.5	200°	80	10k	1pcs/color box 12pcs/case
LED ECO A60/14W/865/E27	14	Ø60 x 119	6500K	1600	114	220 - 240	> 0.5	200°	80	10k	1pcs/color box 12pcs/case

Value LED Lamp Product Codes and Specifications



PAR 38 Directional Lamp



Description	Watt (W)	Dimension (mm)	CCT (K)	Lumen (lm)	LPW	Voltage (V)	P.F	Beam Angle	CRI	Lifetime (hrs)	Qty/Ctn
LED15/P38/830/25/E27	15	Ø122 x 132	3000K	1500	100	220 - 240	> 0.9	25°	80	25k	25pcs
LED15/P38/830/40/E27	15	Ø122 x 132	3000K	1500	100	220 - 240	> 0.9	40°	80	25k	25pcs
LED15/P38/830/60/E27	15	Ø122 x 132	3000K	1500	100	220 - 240	> 0.9	60°	80	25k	25pcs
LED15/P38/840/25/E27	15	Ø122 x 132	4000K	1500	100	220 - 240	> 0.9	25°	80	25k	25pcs
LED15/P38/840/40/E27	15	Ø122 x 132	4000K	1500	100	220 - 240	> 0.9	40°	80	25k	25pcs
LED15/P38/840/60/E27	15	Ø122 x 132	4000K	1500	100	220 - 240	> 0.9	60°	80	25k	25pcs
LED15/P38/865/25/E27	15	Ø122 x 132	6500K	1500	100	220 - 240	> 0.9	25°	80	25k	25pcs
LED15/P38/865/40/E27	15	Ø122 x 132	6500K	1500	100	220 - 240	> 0.9	40°	80	25k	25pcs
LED15/P38/865/60/E27	15	Ø122 x 132	6500K	1500	100	220 - 240	> 0.9	60°	80	25k	25pcs

PAR 30 Directional Lamp



Description	Watt (W)	Dimension (mm)	CCT (K)	Lumen (lm)	LPW	Voltage (V)	P.F	Beam Angle	CRI	Lifetime (hrs)	Qty/Ctn
LED13/P30/830/25/E27	13	Ø95 x 92	3000K	1000	77	220 - 240	> 0.9	25°	80	25k	25pcs
LED13/P30/830/40/E27	13	Ø95 x 92	3000K	1000	77	220 - 240	> 0.9	40°	80	25k	25pcs
LED13/P30/830/60/E27	13	Ø95 x 92	3000K	1000	77	220 - 240	> 0.9	60°	80	25k	25pcs
LED13/P30/840/25/E27	13	Ø95 x 92	4000K	1000	77	220 - 240	> 0.9	25°	80	25k	25pcs
LED13/P30/840/40/E27	13	Ø95 x 92	4000K	1000	77	220 - 240	> 0.9	40°	80	25k	25pcs
LED13/P30/840/60/E27	13	Ø95 x 92	4000K	1000	77	220 - 240	> 0.9	60°	80	25k	25pcs
LED13/P30/865/25/E27	13	Ø95 x 92	6500K	1000	77	220 - 240	> 0.9	25°	80	25k	25pcs
LED13/P30/865/40/E27	13	Ø95 x 92	6500K	1000	77	220 - 240	> 0.9	40°	80	25k	25pcs
LED13/P30/865/60/E27	13	Ø95 x 92	6500K	1000	77	220 - 240	> 0.9	60°	80	25k	25pcs

PAR 20 Directional Lamp



Description	Watt (W)	Dimension (mm)	CCT (K)	Lumen (lm)	LPW	Voltage (V)	P.F	Beam Angle	CRI	Lifetime (hrs)	Qty/Ctn
LED7/P20/830/25/E27	7	Ø63 x 77	3000K	500	77	220 - 240	> 0.9	25°	80	25k	25pcs
LED7/P20/830/40/E27	7	Ø63 x 77	3000K	500	77	220 - 240	> 0.9	40°	80	25k	25pcs
LED7/P20/830/60/E27	7	Ø63 x 77	3000K	500	77	220 - 240	> 0.9	60°	80	25k	25pcs
LED7/P20/840/25/E27	7	Ø63 x 77	4000K	500	77	220 - 240	> 0.9	25°	80	25k	25pcs
LED7/P20/840/40/E27	7	Ø63 x 77	4000K	500	77	220 - 240	> 0.9	40°	80	25k	25pcs
LED7/P20/840/60/E27	7	Ø63 x 77	4000K	500	77	220 - 240	> 0.9	60°	80	25k	25pcs
LED7/P20/865/25/E27	7	Ø63 x 77	6500K	500	77	220 - 240	> 0.9	25°	80	25k	25pcs
LED7/P20/865/40/E27	7	Ø63 x 77	6500K	500	77	220 - 240	> 0.9	40°	80	25k	25pcs
LED7/P20/865/60/E27	7	Ø63 x 77	6500K	500	77	220 - 240	> 0.9	60°	80	25k	25pcs