

Silber Series

Housing and Trim: Die-cast aluminium
 Mounting type: Surface
 Heat Management: Die-cast aluminium heat sink
 Reflector: Aluminium
 Beam angle: 15/24/36/60
 Diffuser: Clear PMMA

LED Modules
 GERMAN Technology
 Comfort COB - Up to 4200lm
 Long service life time : 50,000 hours (L80/B10)
 Ambient temperature - 40°C to +40°C

Drivers: 350mA / 500mA / 700mA /800mA
 (optional: Dimmable available)
 Power factor at full load : 0.97
 SELV , Low Ripple current < 1% ,THD <15%
 Warranty: 5 years

Standards
 EN 620301: LED modules for general lighting - Safety specification
 EN 62471: Photobiological safety of lamps and systems
 EN 55015: Radio disturbance emissions
 EN 61000-3-2 Limited for harmonic emissions
 EN 61547: Immunity requirements



Powered by:



Application: Commercial Building, Lobby, Conventional Hall, Ballroom, Concourse

Model	Wattage	Voltage	Frequency	Power Factor	Colour	Colour Temperature	Module Luminous Flux (Lm)	Module Efficacy Lm/W	Typ. Beam Angle	Typ. CRI Ra	Energy Efficiency	Dimension (Dia x H) mm
ST1-12W	12.2W	220-240	50/60Hz	0.95	Warm white	2700K	1720	141	15° 24° 36° 60°	>82	A+	70 x 123
		220-240	50/60Hz	0.95	Warm white	3000K	1810	149	15° 24° 36° 60°	>82	A+	
		220-240	50/60Hz	0.95	Neutral white	4000K	1865	153	15° 24° 36° 60°	>82	A+	
		220-240	50/60Hz	0.95	Cool white	5700K	1885	155	15° 24° 36° 60°	>82	A+	
ST1-18W	18.1W	220-240	50/60Hz	0.95	Warm white	2700K	2310	127	15° 24° 36° 60°	>82	A+	70 x 123
		220-240	50/60Hz	0.95	Warm white	3000K	2430	134	15° 24° 36° 60°	>82	A+	
		220-240	50/60Hz	0.95	Neutral white	4000K	2505	138	15° 24° 36° 60°	>82	A+	
		220-240	50/60Hz	0.95	Cool white	5700K	2530	139	15° 24° 36° 60°	>82	A+	
ST1-25W	25.1W	220-240	50/60Hz	0.95	Warm white	2700K	3445	137	15° 24° 36° 60°	>82	A+	90 x 150
		220-240	50/60Hz	0.95	Warm white	3000K	3625	144	15° 24° 36° 60°	>82	A+	
		220-240	50/60Hz	0.95	Neutral white	4000K	3660	146	15° 24° 36° 60°	>82	A+	
		220-240	50/60Hz	0.95	Cool white	5000K	3730	148	15° 24° 36° 60°	>82	A+	
		220-240	50/60Hz	0.95	Cool white	5700K	3765	150	15° 24° 36° 60°	>82	A+	
ST1-29W	29.2W	220-240	50/60Hz	0.95	Warm white	2700K	3830	131	15° 24° 36° 60°	>82	A+	90 x 150
		220-240	50/60Hz	0.95	Warm white	3000K	4035	138	15° 24° 36° 60°	>82	A+	
		220-240	50/60Hz	0.95	Neutral white	4000K	4075	140	15° 24° 36° 60°	>82	A+	
		220-240	50/60Hz	0.95	Cool white	5000K	4155	142	15° 24° 36° 60°	>82	A+	
		220-240	50/60Hz	0.95	Cool white	5700K	4195	144	15° 24° 36° 60°	>82	A+	

*Colour tolerance: 3 MacAdam **Production tolerance of luminous flux and efficiency: ±10% ***Min. CRI ±3% ****Power consumption: ±10%
 The values contained in this data sheet can change due to technical innovations without notifications, therefore kindly refer to us when during order.